

ELASTOCOL STICK H2O

Product Description

Polymer emulsion-based primer designed to improve the adhesion of self-adhesive waterproofing membranes on most substrates.

Particularly recommended when the use of solvent-based primer is not advised.

Availability

19 L pails.

Shelf life:

Up to 12 months in original sealed containers.

Storage temperature:

5 to 40°C. Do not freeze!

Health and Safety

Please refer to the MSDS for First Aid Information.

Most current MSDS's can be found on the WaterBlock website at www.waterblocksystems.com or customer service at 1-888-610-2151.

Warranty (10 year Limited)

Please refer to the warranty on our website at www.waterblocksystems.com for more detailed information on our 10 year limited warranty.

Manufacturer

International Building Components, Inc.

21428 Woods Creek Road
Monroe, WA, 98272 USA
Telephone - (360)794.2151
Fax - (360)863.8434
Toll Free - 1.888.610.2151
Web - www.waterblocksystems.com



Cleaning

Uncured material can be cleaned with water. Cured material is best removed by solvents such as mineral spirits, varsol, xylene, etc.

Particular indications

CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.

Properties

Properties	ELASTOCOL Stick H2O
Specific gravity at 20°C (kg/l)	1.00
Solids by Weight (%)	55
Color	Blue
Viscosity (cP)	500
Drying time temperature	30 minutes to 3 hours

(All Values are nominal)

Installation

The substrate must be clean, dry and free of dust, grease or other contaminant.

ELASTOCOL STICK H2O may be applied with a paint brush, roller or sprayer on metal, concrete, wood or polystyrene surfaces as well as on gypsum plasterboard.

Average coverage: 0.1 to 0.3 L/m² (0.25 to 0.75 US gal/100 ft²).

Spraying equipment recommendations:

- Spray tip size: between 20 and 25 mils
- Pressure: 1300 psi continuous

Membranes must be installed on the same day as the application of **ELASTOCOL STICK H2O**.

Minimum application temperature: 5 °C (41 °F)

Minimum Application Temperature: 5°C (41°F).

Limitations: Not suitable for plastic surfaces such as vinyl siding or water repellent-treated panels. Do not use to seal self-adhesive membrane joints, as a primer between two membranes or on asphaltic boards

NOTE: International Building Components Inc. may modify the composition and/or utilisation of its products without prior notice. Consequently orders will be filled according to the latest specification.