

NAIL-ON FLASHING

Product Description

Constructed from heavy weight woven Polypropylene mat, laminated between two layers of UV resistant polypropylene, blended with specialty resins to create the **STRONGEST, MOST DURABLE, INORGANIC, FUNGI RESISTANT, UV RESISTANT, LOW COST** flexible nail on window and door flashing available.

While most manufacturers only perform the minimum amount of ASTM tests required to meet the basic industry requirements, we wanted to be sure we not only surpassed the minimum requirements, but **SET NEW STANDARDS** with superior performance characteristics to provide you with the **BEST LOW COST FLEXIBLE NAIL ON WINDOW AND DOOR FLASHING** you can buy!

Availability

Sizes:
 9", 12" and 18" roll widths by 300' length.

Health and Safety


Please refer to the MSDS for First Aid Information. Most current MSDS's can be found on the WaterBlock website at www.waterblocksystems.com or call customer service at 1-888-610-2151.

Warranty (10 year Limited)

Please refer to the warranty on our website at www.waterblocksystems.com for more detailed information on our 10 year limited warranty.

Manufacturer

International Building Components, Inc.
 21428 Woods Creek Road
 Monroe, WA, 98272 USA
 Telephone - (360)794.2151
 Fax - (360)863.8434
 Toll Free - 1.888.610.2151
 Web - www.waterblocksystems.com



FEATURES

- Approved for usage per ASTM E2112-01
Standard Practice for installation of Exterior Windows and Doors
- Superior Moisture Resistance
Exceeds ASTM D779 Water Resistance test by 300%
- Zero Fungal Growth per ASTM G21-96
Zero is the best score you can receive
- 100% Mold and Mildew Resistant
- Will not Delaminate
- Tear Resistant
- Super Strong
- UV Resistant
- 100% Inorganic
- Economical Cost
- Fast and Easy Installation
Nail or Staple

Properties

Properties	Standards	Nail On
Fungal Resistance	ASTM G21	0 Rating after 28 days
Water Vapor Permeance	ASTM F1249	Less than 0.1 perms
Water Resistance (2)	ASTM D779	120 hrs
Grab Tensile	ASTM D5034	Warp 150 lb / Weft 130 lb
Strip Tensile	ASTM 5035/D828	MD 105 lb/in / CD 80 lb/in
Tongue Tear	ASTM D2261	Warp 40 lb / Weft 35 lb
Trapezoidal Tear	ASTM D4533	Warp 40 lb / Weft 35 lb
Mullen Burst	ASTM D3786	230 psi
Low Temp Bend	ASTM D2136	Passes at -40 degrees
Accelerated UV Weathering (1)	ASTM G53	>90% strength after 2000 hrs

(1) Q.U.V. (A-340) lamps: 8hrs UV @ 60° C; 4hrs condensation @ 50° C
 (2) Less than 1% Dry Indicator color change after 120hrs

Installation

Please see the WaterBlock General Installation Guide available online.

