

SOPRAMASTIC

Product Description

SOPRAMASTIC is a black, solvent-based mastic containing SBS modified bitumen, fibres and mineral fillers. It is an ideal complement for bituminous waterproofing membranes and is used as jointing mastic, caulking material and joint filler. It is compatible with bituminous materials and ensures good waterproofing.

SOPRAMASTIC is a multi-purpose mastic that has been formulated with a high level of polymer in order to resist flow at high temperatures. Furthermore, it is easy to manipulate at temperatures down to -10°C .

Availability

310 ml (20 per boxes) & 800 ml cartridges, and 10 L pails.

Shelf life:

Up to 12 months in original sealed containers.

Health and Safety

Please refer to the MSDS for First Aid Information. Most current MSDS's can be found on the WaterBlock website at www.waterblocksystems.com or call customer service at 1-888-610-2151.

Warranty (10 year Limited)

Please refer to the warranty on our website at www.waterblocksystems.com for more detailed information on our 10 year limited warranty.

Manufacturer

International Building Components, Inc.
21428 Woods Creek Road
Monroe, WA, 98272 USA
Telephone - (360)794.2151
Fax - (360)863.8434
Toll Free - 1.888.610.2151
Web - www.waterblocksystems.com



Cleaning

Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

Particular indications

SOPRAMASTIC is a flammable product. Store in a cool, dry area.

CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.

Properties

Properties

Specific gravity at 20°C (kg/l)	1.12
Color	Black
Application Temperature Range ($^{\circ}\text{C}$)	-10 to 35 (14 to 95°F)
Service Temperature Range ($^{\circ}\text{C}$)	-40 to 80 (-40 to 175°F)
Solids by Weight (%)	83
Flash point (ASTM D-93)	25°C (77°F)
Setting time Between	4 and 24 hours depending on temperature and quantity applied.

(All Values are nominal)

SOPRAMASTIC meets the requirements of CAN/CGSB-37.5-M89 and ASTM D4586 standards.

Installation

SOPRAMASTIC must be applied to clean, sound substrates.

SOPRAMASTIC tubes can be used with a standard cartridge extruder. Excellent adherence on most materials without primer. **Can be applied to damp surfaces.**

NOTE:

International Building Components Inc. may modify the composition and/or utilisation of its products without prior notice. Consequently orders will be filled according to the latest specification.